



Technical data

Substance		
Material	Thermoplastic elastomer (TPE)	
Attribute	Regulation	Value
Colour		blue
Conduit outer diameter		16 mm ; 0.63"
Conduit inner diameter		11 mm ; 0.43"
Application temperature		> -10 °C ; 14 °F
Temperature resistance		permanent -50 °C to 90 °C ; -58 °F to 194 °F
Storage		cool and dry

Area of application

The sealing plugs STOPPA are used for the quick and lasting, secure airtight installation of cables in conduits in accordance with DIN 4108-7. Conduit grommets (e.g. ROFLEX 20 or ROFLEX 20 multi) are available for the airtight connection of conduits to the vapour retarder and airtightness membrane.

Advantages

- ✓ Quick and easy airtight sealing in accordance with DIN 4108-7, SIA 180 and OENORM B8110-2
- ✓ Flexible press-out membrane seals around cables of various diameters
- ✓ Easy to pierce with nails or cartridge nozzles
- ✓ Multi-layered sealing lips ensure optimum connection to profiled pipes
- ✓ Can be used for more than one cable
- ✓ Can be removed at a later date



* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

MOLL
bauökologische Produkte GmbH
 Rheintalstraße 35 - 43
 D-68723 Schwetzingen
 Fon: +49 (0) 62 02 - 27 82.0
 eMail: info@proclima.de

